




Empowering you to work smarter



Compatible with MyNAVAC™ APP

NX1 NX1V Nexus Digital Manifold Gauge



Digital Backlit Display



Folding Hook



Wireless Connection with App & Probes



Impact-Resistant

Aluminum Body

1/4 Turn Ball Valve



Wireless Low & High Temperature Probes

Smart and Precise

Smart and Wireless

- Work with MyNAVAC™ App
- Bluetooth connections with temp probes & micron gauge (sold separately)

Aluminum Body w/ 1/4 Turn Ball Valve

- Reliable, efficient and durable
- Better work experience

Multi-Operation Modes

- Manifold mode with SH/SC display
- Pressure Test mode
- Evacuation mode

Folding Hook

- Hidden hook design
- Easy to transport

Digital and Accurate

- Class 0.4 accuracy with digital display
- Precision at a glance

Impact-Resistant

- Impact-resistant design
- Durable rubber cover

Model	NX1	NX1V
Refrigerant Type	R-11, R-12, R-13, R-22, R-23, R-32, R-113, R-114, R-115, R-116, R-123, R-124, R-125, R134A, R-236FA, R-245FA, R-290, R-401A, R-401B, R-402A, R-402B, R-403B, R-404A, R-406A, R-407A, R-407B, R-407C, R-408A, R-409A, R-410A, R-413A, R-414A, R-414B, R-416A, R-417A, R-417C, R-420A, R-421A, R-421B, R-422A, R-422B, R-422C, R-422D, R-424A, R-427A, R-428A, R-434A, R-437A, R-438A, R-448A, R-449A, R-450A, R-452A, R-452B, R-453A, R-454B, R-458A, R-500, R-501, R-502, R-503, R-507A, R-508B, R-513A, R-600, R-600A, R-601, R-601A, R-744*, R-1233ZD, R-1234YF, R-1234ZE Firmware can be updated at NAVAC website or with MyNAVAC™ App	
Pressure Range	psi	-30 inHg to 720 psi
Power Supply	Rechargeable Li-ion Battery	
Bluetooth Range	feet	Up to 260
Accessory	2 Temperature Probes, Charging Cable, Carry Case	NMV1S Micron Gauge in addition to the NX1 Kit

2-YEAR WARRANTY